EVX Series

EVX 12750 Datasheet

12V Top Terminal VRLA-AGM

Specifications	
Voltage (Vdc)	12
Nominal Capacity (1.75 VPC @25°C)	75 Ah @20hr-rate
Ah Capacity (8-Hr 1.75 VPC @ 25°C)	64.56
Ah Capacity (20-Hr 1.75 VPC @ 25°C)	75
Ah Capacity (8-Hr 1.80 VPC @ 25°C)	63.84
Max Charge Current (A)	22.50
Max Discharge Current (A)	500
Short Circuit Current (A)	1661
Internal Resistance (mΩ)	Approx. 4.7
Terminal Type	B6 terminal to accept M6 bolt
Terminal Torque	51.7±10.3 Kgf·cm / 44.9±9.0 Lbf·in / 5.10±1.0 N·m
Container Material	PP (UL 94-HB)
Weight (kg. / lb., Approx.)	25.60 / 56.38
Length (L) (mm / in)	277.0±2.5 / 10.91±0.10
Width (W) (mm / in)	168.5±2.0 / 6.63±0.08
Height (H) (mm / in)	232.5±2.5 / 9.15±0.10
Design Life	400 cycles @ 100%DOD at 25°C 1800 cycles @ 30%DOD at 25°C
Operating Temperature	Nominal: 25°C (77°F) Discharge: -15°C - 50°C (5°F-122°F) Charge/Storage: -15°C - 40°C (5°F – 104°F)
Float Charging Voltage	--
Eq. Charging Voltage	14.4 - 15.0 Vdc/battery 25°C (77°F)
Self-Discharge	Less than 10% after 90 days, can be stored up to 6 months at 25°C (77°F); Fully recharging is required before usage, and charged sooner if stored at higher temperature than 25°C (77°F).

Valve Regulated Lead Acid (VRLA) Battery

Maintenance-Free, Absorbent Glass Mat (AGM) Technology for Efficient Gas Recombination of up to 99%

Pure Lead Construction and Proprietary Elements

Designed for E-mobility or deep cycling applications

Built in Accordance with IEC 60254-1:2005 / IEC60254-2:2008 and UL1989 Recognized (MH14533)

MH14533

EVX Series

EVX 12750 Datasheet

12V Top Terminal VRLA-AGM

Constant Current Discharge Characteristics Unit: A (25°C, 77°F)												
F.V/Time	**30MIN**	**45MIN**	**60MIN**	**90MIN**	**2HR**	**3HR**	**4HR**	**5HR**	**6HR**	**8HR**	**10HR**	**20HR**
10.02V (1.67 VPC)	81.6	60.3	48.6	35.2	27.6	19.7	15.4	12.7	10.7	8.25	6.74	3.80
10.50V (1.75 VPC)	78.1	57.9	46.8	33.9	26.7	19.2	15.0	12.4	10.5	8.07	6.60	3.75
10.80V (1.80 VPC)	75.8	56.4	45.7	33.2	26.2	18.9	14.8	12.2	10.3	7.98	6.54	3.72

Constant Power Discharge Characteristics Unit: W (25°C, 77°F)												
F.V/Time	**30MIN**	**45MIN**	**60MIN**	**90MIN**	**2HR**	**3HR**	**4HR**	**5HR**	**6HR**	**8HR**	**10HR**	**20HR**
10.02V (1.67 VPC)	906	664	532	386	309	223	175	144	122	94.3	77.0	41.2
10.50V (1.75 VPC)	863	637	513	373	299	216	170	140	119	92.3	75.7	40.7
10.80V (1.80 VPC)	839	620	500	367	293	213	168	139	118	91.3	75.0	40.6