

PA-IEC-LN2.R001



Dimensions

Length	11mm	±1mm
Width	34.5mm	±1mm
Height	55.5mm	±0.5mm



IEC 62133 2nd Ed.

Data for Pack

Nominal voltage	3.6V	2.75V - 4.2V		
Nominal capacity	2350mAh	typical (minimum 2200mAh)		
Used cell in pack	1pcs	Panasonic NCA-103450A		
Internal resistance pack	130mΩ	±10%		
Max charge voltage	4.2V			
Max charge voltage	standard	470mA	0°C < T < 45°C	
	rapid	1500mA	10°C < T < 45°C	
Discharge	standard	470mA	-20°C < T < 60°C *below 0°C with limited performance	
	max. cont.	2200mA	-20°C < T < 60°C *below 0°C with limited performance	
	max. peak	2750mA	-20°C < T < 60°C *below 0°C with limited performance	
Short circuit current	25A	360μs		
NTC	10kΩ	Tolerance 5%; B-value 25°C/85°C = 3980K		
Connector	JST	XHP-3	Pin1	GND (black)
			Pin2	NTC (yellow)
			Pin3	Vbatt (red)
Cable Length	45mm	±5mm		
Weight	42g	±2.5g		
Watt-hour rating	8Wh	acc. to UN38.3 Certificate of cell manufacturer		

Limitations by Safety Unit (SU)

over voltage (per cell)	cut off	4.215V	±0,025V
	release	4.115V	±0,025V
under voltage (per cell)	cut off	2.3V	±0,05V
	release	2.4V	±0,05V
Current Limit 1 by SU		< 2.5A	continuous (typical)
Current Limit 2 by SU		< 20A	t < 2,24ms
Current Limit 3 by SU		48A	320μs (typical)
Power consumption	active	7μA	max. ±5%
	power down	max. 1μA	power down modus only after overcurrent event
ESD Protection		No	

Recommended Charger

C-LIO-1SN05-1,8M-DIN4-GPN-.R001

The data in this datasheet document are for information and descriptive purposes only and are not to make or imply any guarantee or warranty. No guarantee for zero failure status of given information inside this document. Please see/request detailed specification for finally valid data.

For more information and the contact details of the local suppliers, please visit CELLTECH-GROUP.COM