

PA-INB162-C17UL.4.2.R001



Dimensions

Length	73mm
Width	19mm
Height	71mm



IEC62133-2:2017



MH45979

*picture only for reference

Data for Pack

Nominal voltage	7.27V	5V - 8.4V (usable voltage range)			
Nominal capacity	7Ah	typical			
Used cells in pack	4pcs				
Internal resistance pack	77mΩ	±20%			
Charge voltage	8.4V	max ²⁾			
Charge current	standard	1.4A	0°C < T < 45°C ³⁾		
	rapid	3.5A	10°C < T < 45°C ³⁾		
Discharge	standard	1.4A	-20°C < T < 60°C ^{1) 3)}		
	max cont.	5A	-20°C < T < 60°C ^{1) 3)}		
	max peak 1	15A	0°C < T < 40°C ³⁾	t < 5ms	
	max peak 2	30A	0°C < T < 40°C ³⁾	t < 0.2ms	
Over Voltage Cut-off (per cell)	4.215V	safety unit cut-off ± 35mV			
Over Voltage release (per cell)	4.115V	± 35mV			
Under Voltage Cut-off (per cell)	2.4V	typical @Ta 25°C; recovery = charger connect			
Discharge current protection	6.67A	typical @Ta 25°C; recovery = load remove			
Charge current protection	5A	typical @Ta 25°C; recovery = charger remove			
load short circuit protection	54A	typical @Ta 25°C; max 600μs			
non resettable current fuse	7A				
non resettable second over voltage cut-off	4.35V	± 40mV			
non resettable temperature protection	120°C	typical			
Connector	Molex	Microfit 3.0 43645-0300	Pin1	Bat+	red
			Pin2	NTC	yellow
			Pin3	GND	black
Cable Length	124mm	± 5mm			
Weight	195g	± 5%			
Watt-hour rating	50.88Wh	acc. to UN38.3 TSR			

Charging method

CC/CV Charger with NTC temperature control

- 1) below 0°C with limited performance data (current output and available capacity)
- 2) Recommended Charge Voltages: Medical applications = 8.2V; Standby / UPS = 8V
- 3) Cell surface temperature, not ambient

The data in this datasheet document are for information and descriptive purposes only and are not to make or imply any guarantee or warranty. No guarantee for zero failure status of given information inside this document. Please see/request detailed specification for finally valid data.

For more information and the contact details of the local suppliers, please visit CELLTECH-GROUP.COM