

PA-INB33X-C17UL.4.2.R002



Dimensions



Length	66mm
Width	36mm
Height	38mm



IEC62133-2:2017



MH45979 4)

*picture only for reference

Data for Pack

Nominal voltage	3.635V	2.5V - 4.2V (usable voltage range)	
Nominal capacity	10.5Ah	typical	
Used cell in pack	3pcs	18650	
Internal resistance pack	46mΩ	±10% typical value @20°C with fresh cells	
Charge voltage	4.2V	max ²⁾	
Charge current	low temp	2.625A 0°C < T < 10°C ³⁾	
	standard	3A 10°C < T < 45°C ³⁾	
Discharge	standard	3A -20°C < T < 60°C ^{1) 3)}	
	max cont.	3A -20°C < T < 60°C ^{1) 3)}	
Over Voltage Cut-off (per cell)	4.28V	typical @Ta 25°C 'safety unit cut-off	
Over Voltage release (per cell)	4.18V	typical @Ta 25°C	
Under Voltage Cut-off (per cell)	2.3V	typical @Ta 25°C; recovery = charger connect	
Discharge current protection	>4.46A	typical @Ta 25°C; recovery = load remove	
Charge current protection	>4.46A	typical @Ta 25°C; recovery = charger remove	
load short circuit protection	>45A	typical @Ta 25°C; max 300μs	
non resettable current fuse	5A		
non resettable second over voltage cut-off	4.35V		
Connector	JST	XHP-3	Pin1 GND
			Pin2 NTC
			Pin3 BAT+
Cable Length	45mm	± 5mm	
Weight	145g	± 5g	
Watt-hour rating	38.16Wh	acc. to UN38.3 TSR	

Charging method

CC/CV Charger with NTC temperature control

- 1) below 0°C with limited performance data (current output and available capacity)
- 2) Recommended Charge Voltages: Medical applications = 4.1V; Standby / UPS = 4V Standby / UPS = 4V; Do not apply continuous charge (trickle charge) method
- 3) Cell surface temperature, not ambient
- 4) UL conditions of acceptability to be consider in end application

The data in this datasheet document are for information and descriptive purposes only and are not to make or imply any guarantee or warranty
No guarantee for zero failure status of given information inside this document. Please see/request detailed specification for finally valid data.

For more information and the contact details of the local suppliers, please visit CELLTECH-GROUP.COM