

PA-L1022.R006



Dimensions

Length	148	± 1mm
Width	61	± 1mm
Height	98	± 1mm

Data for Pack

Nominal voltage	25.2V	21V - 29.4V				
Nominal capacity	6600mAh	typical				
Used cell in pack	21pcs	LG INR18650-S3				
Internal resistance pack	160mΩ	±10%				
Charge voltage	29.4V	max (via external charger)				
Charge current	1A	-10°C < T < 50°C (internal charger, input 15V - 30V DC)				
	max	5A	0°C < T < 45°C (external charger)			
Discharge	standard	5A	-20°C < T < 70°C *1)			
	max cont.	13A	-20°C < T < 70°C *1)			
	max peak	30A	-20°C < T < 45°C t < 10ms *1)			
Short circuit current	≤ 100A	≤ 100μs				
NTC	10kΩ	Tolerance ±3%; B-value 25°C/85°C = 3980K				
Connector	AMP	Val-U Lok	1: GND	4: SMB Data	7: Pack+	10: NTC
			2: GND	5: SMB Clock	8: Pack+	
			3: GND	6: Pack+	9: DC IN	
Cable Length	n/a					
Weight	1290g	±30g				
Watt-hour rating	166.32Wh	acc. to UN38.3 Certificate				

*1) discharge in ambient temperatures lower than 0°C will result in limited performance in current output and usable capacity

Limitations by Safety Unit (SU) @ Ta 25°C

over voltage (per cell)	cut off	4200mV	±25mV
	release	4100mV	±50mV
under voltage (per cell)	cut off	3000mV	±80mV
	release	3100mV	±80mV
Current Limit 1 by SU	>13.5A	t > 10s typical	
Current Limit 2 by SU	>30A	t > 50ms (typical)	
short circuit protection	>100A	t > 100μs	
Power consumption	active	25mA	max
	sleep	200μA	±20μA

The data in this datasheet document are for information and descriptive purposes only and are not to make or imply any guarantee or warranty. No guarantee for zero failure status of given information inside this document. Please see/request detailed specification for finally valid data.

For more information and the contact details of the local suppliers, please visit CELLTECH-GROUP.COM