

# PA-LN19.R003



## Dimensions

Length	67 mm	± 2 mm
Width	18.5 mm	± 1 mm
Height	22 mm	± 1 mm

## Data for Pack

Nominal voltage	3.6V	3V - 4.2V			
Nominal capacity	2950mAh	typical			
Used cell in pack	1pcs	Panasonic NCR-18650TD			
Internal resistance pack	110mΩ	±10%			
Max charge voltage	4.2V	max.			
Charge current	standard	580mA	10°C < T < 45°C		
	rapid	1950mA	10°C < T < 45°C		
Discharge	standard	580mA	-20°C < T < 60°C *below 0°C with limited performance		
	max. cont.	2200mA	-20°C < T < 60°C *below 0°C with limited performance		
	max. peak	2950mA	-20°C < T < 45°C t < 1ms *below 0°C with limited performance		
Short circuit current	≥22A	> 500μs			
NTC	10kΩ	Tolerance 5%; B-value 25°C/85°C = 3980K			
Connector	JST	XHP-3	Pin1	GND	black
			Pin2	NTC	yellow
			Pin3	PLUS	red
Cable Length	45 mm	± 5 mm			
Weight	ca. 45g	± 5 g			
Watt-hour rating	9.8Wh	acc. to UN38.3 Certificate			

## Limitations by Safety Unit (SU) @ Ta 25°C

over voltage (per cell)	cut off	4275mV	± 25mV
	release	4075mV	± 25mV
under voltage (per cell)	cut off	2300mV	± 0,050 V
	release	3V	± 0,050 V
Current Limit 1 by SU		≤2.2A	continuous
Current Limit 2 by SU		≥2.95A	>2,24 ms
short circuit protection		≤20A	>320μs typical
Power consumption	active	< 12.5μA	@4.2V ±5μA
	shutdown	< 1.5μA	-0/+1μA (when Ubat < 2.25V)

## Recommended Charger

1 Cell CC/CV Charger

The data in this datasheet document are for information and descriptive purposes only and are not to make or imply any guarantee or warranty. No guarantee for zero failure status of given information inside this document. Please see/request detailed specification for finally valid data.

For more information and the contact details of the local suppliers, please visit [CELLTECH-GROUP.COM](http://CELLTECH-GROUP.COM)