

# PA-LNB117.R002



## Dimensions

Length	134	± 1mm
Width	38	± 1mm
Height	25	± 1mm



MH45979



IEC 62133 2nd. Ed.

## Data for Pack

Nominal voltage	14.4V	12V - 16.8V ( 12V - 16.4V @ medical applications)				
Nominal capacity	3350mAh	typical (3100mAh minimum)				
Used cell in pack	4pcs	Panasonic NCR-18650B				
Internal resistance pack	150mΩ	±10%				
Max charge voltage	16.8V					
Charge current	max	1625mA	10°C < T < 45°C			
Discharge	standard	500mA	-20°C < T < 60°C *below 0°C with limited performance			
	max cont.	4.875A	0°C < T < 45°C *below 0°C with limited performance			
	max peak	5A	-20°C < T < 45°C t < 1ms *below 0°C with limited performance			
Short circuit current	~ 96A	< 915μs				
NTC	n/a					
Connector	Molex	Microfit 43645-0400	Pin1	Bat+	Pin4	GND
			Pin2	SCL		
			Pin3	SDA		
Cable Length	135mm	± 5mm				
Weight	ca. 220g	± 5g				
Watt-hour rating	48Wh	acc. to UN38.3 Certificate from cell				

## Limitations by Safety Unit (SU) @ Ta 25°C

over voltage (per cell)	cut off	4225mV	±25mV
	release	4050mV	±25mV
under voltage (per cell)	cut off	3000mV	±50mV
	release	3300mV	±50mV
Current Limit 1 by SU		≥5A	≥16s typical
Current Limit 2 by SU		≥14A	≥31ms typical
short circuit protection		≥22.5A	≥ 915μs typical
Power consumption	active	350μA	@16.8V ±50μA
	sleep	< 50μA	max.
ESD Protection		YES	

## Recommended Charger

SBS Compliant 4S CC/CV Charger

The data in this datasheet document are for information and descriptive purposes only and are not to make or imply any guarantee or warranty. No guarantee for zero failure status of given information inside this document. Please see/request detailed specification for finally valid data.

For more information and the contact details of the local suppliers, please visit [CELLTECH-GROUP.COM](http://CELLTECH-GROUP.COM)