

# PA-LNB217.R002



## Dimensions

Length	134mm	± 1mm
Width	38	± 1mm
Height	43	± 1mm

\*Image only for reference, battery has 4pin connector

## Data for Pack

Nominal voltage	14.4V	12V - 16.8V ( max. 16,4 in medical application / long term use)				
Nominal capacity	6700mAh	typical @ 4,2V / cell / (6200mAh @ 4,1V / cell)				
Used cell in pack	8pcs	Panasonic NCR-18650BF				
Internal resistance pack	100mΩ	±10%				
Max charge voltage	16.4V					
Charge current	standard	1.6A	0°C < T < 45°C			
	rapid	3A	10°C < T < 45°C			
Discharge	standard	1.3A	-20°C < T < 60°C * <sup>1)</sup>			
	max cont.	5A	0°C < T < 45°C * <sup>1)</sup>			
	max peak	14A	-20°C < T < 45°C t < 5ms * <sup>1)</sup>			
Short circuit current	50A	< 300μs				
NTC	n/a	temperature can be read out via SMBus				
Connector	Molex	Microfit	Pin1	Bat+	Pin4	GND
			Pin2	SCL		
			Pin3	SDA		
Cable Length	135mm	± 5mm				
Weight	310g	± 5g				
Watt-hour rating	96Wh	acc. to UN38.3 Certificate				

\*<sup>1)</sup> discharge in ambient temperatures lower than 0°C will result in limited performance in current output and usable capacity

## Limitations by Safety Unit (SU) @ Ta 25°C

over voltage (per cell)	cut off	4100mV	± 25mV
	release	4050mV	± 25mV
under voltage (per cell)	cut off	3000mV	± 50mV
	release	3300mV	± 50mV
Current Limit 1 by SU	≥5A	continuous	
Current Limit 2 by SU	≥14A	>31ms typical	
short circuit protection	≥22.5A	>915μs typical	
Power consumption	active	< 350μA	max
	sleep	< 50μA	max

## Recommended Charger

Smart Charger, SBS compatible

The data in this datasheet document are for information and descriptive purposes only and are not to make or imply any guarantee or warranty. No guarantee for zero failure status of given information inside this document. Please see/request detailed specification for finally valid data.

For more information and the contact details of the local suppliers, please visit [CELLTECH-GROUP.COM](http://CELLTECH-GROUP.COM)