

PA-LS419.R001



*picture only for reference

Dimensions

Length	45.5mm	± 1mm
Width	19.7 mm ⁽¹⁾	± 1mm
Height	71mm	± 1mm

(1) swelling after 600 cycles up to 1.6mm

Data for Pack

Nominal voltage		3.65V	2.5V - 4.2V					
Nominal capacity		4Ah	typical					
Used cell in pack		1pcs	Saft MP174565 integration XTD					
Internal resistance pack		100mΩ	±10%					
Max charge voltage		4.2V	max.					
Charge current	standard	0.8A	-30°C < T < 85°C					
	rapid	3A	-30°C < T < 85°C *limited by connector					
Discharge	standard	0.8A	-40°C < T < 85°C					
	max. cont.	3A	-40°C < T < 85°C *limited by connector					
	max. peak	12A	-40°C < T < 85°C t < 2ms					
Short circuit current		≤ 24A	< 320 μs					
NTC		10kΩ	Tolerance 5%; B-value 25°C/85°C = 3980K					
Connector	Hersteller	Type	Pin1	Bat+	red	Pin4	NTC	white
			Pin2	nc	blue	Pin5	GND	black
			Pin3	nc	yellow			
Cable Length		70mm	± 5 mm					
Weight		105g	± 5g					
Watt-hour rating		15Wh	acc. to UN38.3 Certificate from cell manufacturer					

1) below 0°C with limited performance in current output and available capacity 2) Cell temperature, not ambient temperature

Limitations by Safety Unit (SU) @ Ta 25°C

over voltage (per cell)	cut off	4.215V	± 0.025V
	release	4.115V	± 0.025V
under voltage (per cell)	cut off	2.3V	± 0.05V
	release	2.4V	± 0.05V
Current Limit 1 by SU		3.8A	t < 9ms
Current Limit 2 by SU		12.4A	t < 2.24ms
short circuit protection		≤ 24A	< 320μs typical
Power consumption	active	70μA	max. 100μA
	shutdown	10 μA	max. 25μA

Recommended Charger

C-LIO-1SN15-1.8M_DIN4GPN.R001

The data in this datasheet document are for information and descriptive purposes only and are not to make or imply any guarantee or warranty. No guarantee for zero failure status of given information inside this document. Please see/request detailed specification for finally valid data.

For more information and the contact details of the local suppliers, please visit CELLTECH-GROUP.COM